

Project:	Type:
	Comments:



Highlights


The TechoLED BX series features specification-grade linear LED fixtures made from high-grade aluminum extrusions. Available in standard sizes from 2 to 8 feet, as well as custom lengths, these fixtures can be pendant, surface, or wall-mounted. With virtually limitless options for creating patterns and shapes, the BX series provides a versatile, cost-effective, and modern lighting solution.

LED: Samsung LED chips, 2700-5000K, tunable white and RGB/RGBW available, 90CRI, 50,000 hour rated lifespan. Custom lumen packages available.


Optical: Direct and direct/indirect illumination, 110° beam angle, UGR<19

Construction: Damp location listed, high grade aluminum extrusion, die cast end caps, PMMA diffuser, powder coat finish. X, T, L lit corners, wall to ceiling transitions, for smooth seamless patterns.

Cross Section



Installation



Project:	Type:
	Comments:

Configuration Example

Model #	Distribution	Length	Lumen Output	Color Temp.	Voltage	Color
TECHOLED-BX-2U-D-2-LO-27-U-W	Direct	2'	Low	2700K	110-277V	White

Ordering Guide:

Select one option from each group below. For a custom preference please contact sales@techoled.com

1-FIXTURE ID	2-DISTRIBUTION	3-LENGTH	4-LUMEN OUTPUT
BX-2U BX-2U	D Direct	2 2'	LO Low
	DI Direct/Indirect	4 4'	ME Medium
	DI2 D/I2-circuit	6 6'	HI High
		8 8'	
		C Custom	

5-COLOR TEMP.	6-VOLTAGE	7-FINISH	8-MOUNTING
27 2700K	U 110-277V	S Silver	P Pendant
30 3000K	HV 347V	W White	W Wall Mount
35 3500K		B Black	SM Surface Mount
40 4000K		C Custom (RAL#)	
50 5000K			
DT Lutron T-series			
RGB RGB			
RGBW RGBW			
D Tunable White			

9-DRIVER OPTIONS	10-OPTIONS	11-OPTIONS (CONT.)
DM 0-10V Dimming	RF-D Remote Tunable (RF only)	EM EM Battery (remote)
2C 2 Channel	RF-R Remote RGB/W (RF only)	X None
DM1% 1% Dimming	M Motion Sensor (remote)	
LT1 LDE1 Lutron 1%	BM BubblyNet BT Mesh	
DA Dali	CS Casambi	
DMX DMX	AWN R Lutron Athena Node	
TR Triac Dimming	AWN S Lutron Athena Node sensor	
RF RF Wireless	NL-ES7 nLight - Wired	
X None	NL-AIR nLight - AIR	
	NL-M nLight - Module only	
	X None	

Project:	Type:
	Comments:

Lumen Output Details

Model #	Size	Output	Color Temp.	Wattage	Lumen Output
TECHOLED-BX-2U-D-2-LO-30	2'	Low	3000K	12W	1160Lm
TECHOLED-BX-2U-D-2-ME-30	2'	Medium	3000K	18W	1800Lm
TECHOLED-BX-2U-D-2-HI-30	2'	High	3000K	23W	2300Lm
TECHOLED-BX-2U-D-4-LO-30	4'	Low	3000K	23W	2320Lm
TECHOLED-BX-2U-D-4-ME-30	4'	Medium	3000K	36W	3600Lm
TECHOLED-BX-2U-D-4-HI-30	4'	High	3000K	46W	4600Lm
TECHOLED-BX-2U-D-6-LO-30	6'	Low	3000K	35W	3480Lm
TECHOLED-BX-2U-D-6-ME-30	6'	Medium	3000K	54W	5400Lm
TECHOLED-BX-2U-D-6-HI-30	6'	High	3000K	69W	6900Lm
TECHOLED-BX-2U-D-8-LO-30	8'	Low	3000K	46W	4640Lm
TECHOLED-BX-2U-D-8-ME-30	8'	Medium	3000K	72W	7200Lm
TECHOLED-BX-2U-D-8-HI-30	8'	High	3000K	92W	9200Lm

Performance above applies to 90 CRI, 3000K. Calculate 96% for 2700K, 104% for 3500K and 109% for 4000K

Model #	Size	Output	Color Temp.	Wattage	Down Lumen Out.	Up Lumen Out.
TECHOLED-BX-2U-DI-2-LO-30	2'	Low	3000K	17W	1160Lm	570Lm
TECHOLED-BX-2U-DI-2-ME-30	2'	Medium	3000K	23W	1800Lm	900Lm
TECHOLED-BX-2U-DI-2-HI-30	2'	High	3000K	30W	2300Lm	1150Lm
TECHOLED-BX-2U-DI-4-LO-30	4'	Low	3000K	34W	2320Lm	1160Lm
TECHOLED-BX-2U-DI-4-ME-30	4'	Medium	3000K	46W	3600Lm	1800Lm
TECHOLED-BX-2U-DI-4-HI-30	4'	High	3000K	60W	4600Lm	2300Lm
TECHOLED-BX-2U-DI-6-LO-30	6'	Low	3000K	51W	3480Lm	1740Lm
TECHOLED-BX-2U-DI-6-ME-30	6'	Medium	3000K	68W	5400Lm	2700Lm
TECHOLED-BX-2U-DI-6-HI-30	6'	High	3000K	90W	6900Lm	3450Lm
TECHOLED-BX-2U-DI-8-LO-30	8'	Low	3000K	68W	4640Lm	2320Lm
TECHOLED-BX-2U-DI-8-ME-30	8'	Medium	3000K	91W	7200Lm	3600Lm
TECHOLED-BX-2U-DI-8-HI-30	8'	High	3000K	120W	9200Lm	4600Lm

Performance above applies to 90 CRI, 3000K. Calculate 96% for 2700K, 104% for 3500K and 109% for 4000K

Performance

Output	Direct			Indirect		
	Lumens / W	W / ft	Lumens / ft	Lumens / W	W / ft	Lumens / ft
Low	100	5.8	580	100	2.9	290
Medium	100	9.0	900	100	4.5	450
High	100	11.5	1150	100	5.8	575

Project:	Type:
	Comments:

Driver Option Details


Code	Description
LT1	LDE1 -Lutron Hi-lume 1% EcoSystem, Soft-on, Fade-to Black Dimming
DA	DALI
DMX	DMX - Decoder provided by TechoLED, controller by others

Controls Details

Code	Description
RF-D	RF Wireless remote controller for tunable white. Default for tunable white.
RF-R	RF Wireless remote controller for RGB & RGBW. Default for RGB & RGBW.
M	Motion Sensor - remote, for integral sensor consult factory
BM	Bluetooth Mesh Smart Wireless Control by BubblyNet
CS	Bluetooth Mesh Smart Wireless Control by Casambi
AWNR	Lutron Athena wireless node
AWNS	Lutron Athena wireless node with sensor
NL-ES7	Acuity nLight – Wired nES7 sensor
NL-AIR	Acuity nLight – AIR wireless rES7 sensor
NL-M	Acuity nLight - ready, sensor by others

Project:	Type:
	Comments:


Dimension and Mounting - Direct Distribution (D)




FIXTURE ID	A	B	C	D	E
BX-2U-D-2	3.5"	2.6"	24.2"	4.33"	0.98"
BX-2U-D-4	3.5"	2.6"	48"	4.33"	0.98"
BX-2U-D-6	3.5"	2.6"	71.7"	4.33"	0.98"
BX-2U-D-8	3.5"	2.6"	95.5"	4.33"	0.98"

Project:	Type:
	Comments:


■ Pendant Mount (D)




■ Pendant Kit



■ Surface Mount (D)





■ Surface Mount Kit




Project:	Type:
	Comments:

■ Wall Mount (D)




■ Wall Mount Kit



Project:	Type:
	Comments:



Dimension and Mounting - Direct/Indirect Distribution (DI)




FIXTURE ID	A	B	C	D	E
BX-2U-DI-2	3.5"	2.6"	24.2"	4.33"	0.98"
BX-2U-DI-4	3.5"	2.6"	48"	4.33"	0.98"
BX-2U-DI-6	3.5"	2.6"	71.7"	4.33"	0.98"
BX-2U-DI-8	3.5"	2.6"	95.5"	4.33"	0.98"

Project:	Type:
	Comments:



■ Pendant Mount (DI)




■ Pendant Kit



■ Wall Mount (DI)




■ Wall Mount Kit




Project:	Type:
	Comments:

Connectors




Project:	Type:
	Comments:


Photometrics




TECHOLED-BX-2U-D-2-LO-30




TECHOLED-BX-2U-D-2-ME-30




TECHOLED-BX-2U-D-2-HI-30




TECHOLED-BX-2U-D-4-LO-30




TECHOLED-BX-2U-D-4-ME-30




TECHOLED-BX-2U-D-4-HI-30




TECHOLED-BX-2U-D-6-LO-30




TECHOLED-BX-2U-D-6-ME-30




TECHOLED-BX-2U-D-6-HI-30



TECHOLED-BX-2U-D-8-LO-30




TECHOLED-BX-2U-D-8-ME-30




TECHOLED-BX-2U-D-8-HI-30


Project:	Type:
	Comments:




TECHOLED-BX-2U-DI-2-LO-30




TECHOLED-BX-2U-DI-2-ME-30




TECHOLED-BX-2U-DI-2-HI-30




TECHOLED-BX-2U-DI-4-LO-30




TECHOLED-BX-2U-DI-4-ME-30




TECHOLED-BX-2U-DI-4-HI-30




TECHOLED-BX-2U-DI-6-LO-30




TECHOLED-BX-2U-DI-6-ME-30




TECHOLED-BX-2U-DI-6-HI-30



TECHOLED-BX-2U-DI-8-LO-30




TECHOLED-BX-2U-DI-8-ME-30




TECHOLED-BX-2U-DI-8-HI-30

Project:	Type:
	Comments:


Patterns Option Examples



Rectangle



L-Shape



Custom


Project:	Type:
	Comments:

Finish Details (powder coat finish)

■ Standard Colors




■ Custom Colors



Any RAL color available, please refer to ralcolorchart.com


■ Custom Wooden Colors



Project:	Type:
	Comments:

Color Temperature

Color Temperature



Tunable White

